

PS53 - Height Endurance Helmet

Collection: Head Protection

Range: PPE

Materials: ABS

Product information

Designed to be specially used when working at heights. Light and comfortable, this peak-less helmet is compact featuring an ABS shell, textile comfort harness 6 points and wheel ratchet adjustment, size 52-63cm. Improved technical sweat band and 4 points chin strap (Y style) with soft rubber chin protector included.

ANSI/ISEA Z89.1 TYPE I (Class E)
EN 50365 Class:0
EN 397 (-30°C/+50°C)

Head Protection

PW rapidly expanding head protection product range aims to benefit our customers by combining the most updated styles and standards in head protection, irrespective of job or location. A wide selection of compatible accessories is also available. A full explanation of features and performances are given in order to help you make a more informed choice.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Features

- CE-CAT III
- Light and robust
- Specially designed for working at height
- Electrical insulation up to 1000Vac or 1500Vdc (EN 50365)
- 6 points textile harness
- Wheel ratchet size adjustment for easy fitting
- Hi-Visibility colour for visibility in daylight
- Chin strap included
- Compatible with PW47 and PS47 Clip-On Ear Muff
- Compatible accessories available



Colours

| | Range |
|---------------|-------|
| White | - |
| Hi-Vis Yellow | - |
| Blue | - |
| Black | - |
| Hi-Vis Orange | - |

PORTWEST[®]

PRODUCT SPECIFICATION & TECHNICAL DATA

PS53 - Height Endurance Helmet

Commodity Code: 6506101000

Test House

Inspec (Notified Body No.: 0194)

56 Leslie Hough Way

M66AJ, UK

Cert No: 2797

| Item | Colour | Len | Wid | Hgt | Weight (Kg) | Cubic (m ³) | EAN13 | DUN14 |
|---------|--------|------|------|------|-------------|-------------------------|---------------|----------------|
| PS53ORR | Orange | 57.0 | 45.0 | 50.0 | 0.4600 | 0.1283 | 5036108262595 | 15036108751690 |